

Rail drilling machine

RAIL.60S

Available in 6 different rail adapter versions:
S49, S54, TRC68, UIC50, UIC54 and UIC60.

Technical data

| | Metric | Imperial |
|------------------------------|---|--------------------|
| Annular cutting | Ø 12 - 36 mm | Ø 7/16" - 1 7/16" |
| Length | 262 mm | 10 5/16" |
| Width | 130 mm | 5 1/8" |
| Height | 597 - 747 mm | 23 1/2" - 29 7/16" |
| Stroke | 170 mm | 6 11/16" |
| Weight* | 14.4 kg | 31.7 lbs |
| Motor power | 1,600 W | 14.5 A |
| Total power | 1,700 W | 15.5 A |
| Speed (no load) | (I) 60 - 275 rpm (II) 100 - 500 rpm | |
| Speed (load 1,600 W, 14.5 A) | (I) 60 - 275 rpm (II) 100 - 500 rpm | |
| Spindle (Weldon) | MT3 19.05 mm | MT3 3/4" |
| Voltage | 110 - 120 V / 60 Hz 220 - 240 V / 50 - 60 Hz | |

* Without power cord and handles



Features:



Adjustable
speed



Overheat
protection



Oil lubricated
gearbox

Benefits:

- Suitable for processing rails
- High-accuracy capstan hub
- Morse Taper 3 spindle
- Integrated slide and two-speed oil lubricated gearbox for:
 - High accuracy
 - Enlarged lifecycle
 - Minimal vibration
- High-precision height adjustment for:
 - Low maintenance
 - Minimal wear correction